

# Technical Datasheet

Revision-Nr: 1  
Date of issue: 04.02.2009  
Last change: 30.05.2013

## CTK 300 Aqueous Detergent

This sheet supersedes the one dated: 04.02.2009

Changes are characterized by a marginal vertical line

**Description:** Detergent for the wash and rinse tanks used to process Methacrylate based Porosity Sealants.

### Physical data of liquid additive:

**Appearance:** Colourless to light yellow and clear

**Recommended uses  
And Concentrations** Multi-Metal Neutral Wash and Rinse Tank Detergent Booster.  
Use for Mild Steel, Cast Iron, Brass, Copper and Aluminium.  
Use in Wash and Rinse tanks at between 0.1 to 1.0%.

**Smell:** Pleasant ester like odour

**Flammable point:** 102°C (DIN 51758)

**pH** pH 6 – 8 (0.1 to 1.0%)

**Density at 20°C:** 1.000 – 1.100 g/ml

**Solubility in water:** Fully Miscible

**Storage conditions\*:** 12 months at max. 35°C  
Minimal temperature of storage: 0°C  
Recommendation: aerate regularly by opening the cork.  
Modifications through metals, alkalis, peroxides and direct sunlight  
(\* in original packaging; do not keep under inert gas

All information given herein corresponds to our latest status of knowledge. This information is neither a guarantee for product properties nor legally binding. TÜV certificate for the production of the products of impregnation according to DIN ISO 9001 / EN 29001 since 1993; in the new version according to DIN IN ISO 9001:2008 since 2009